



HOSPITAL GRADE SILENCER 35-42 dB												
CATALYTIC SILENCER HOUSING PN	CATALYST NOMINAL DIAMETER	INLET NOZZLE NOMINAL DIAMETER (IN)	SILENCER SHELL DIAMETER (IN)	OVERALL LENGTH (IN)	INLET TO OUTLET LENGTH (IN)	CENTER LINE TO INLET LENGTH (IN)	INLET NOZZLE LENGTH (IN)	OUTLET NOZZLE LENGTH (IN)	ACCESS DOOR NOMINAL HEIGHT (IN)	ESTIMATED HOUSING WEIGHT (LB)	OUTLET DIRECTION AS VIEWED FROM INLET (Right or Left)	
P	D	L	S	K	NI	No	R					
18-510305	14.50	6	22.2	106	91	18	4.5	4.5	16	460	R	
18-510306	14.50	8	26.3	109	93	23	8.0	4.5	18	640	R	
18-510307	14.50	10	30.3	134	118	25	8.0	4.5	20	870	R	
18-510308	17.00	6	22.2	109	93	18	4.5	4.5	16	470	R	
18-510309	17.00	8	26.3	109	92	20	4.5	4.5	18	650	R	
18-510310	17.00	10	30.3	134	116	25	8.0	4.5	20	880	R	
18-510311	17.00	12	36.3	136	117	28	8.0	4.5	23	1190	R	
18-510312	19.50	8	26.3	110	92	20	4.5	4.5	18	650	R	
18-510313	19.50	10	30.3	134	115	22	4.5	4.5	20	880	R	
18-510314	19.50	12	36.3	136	116	28	8.0	4.5	23	1200	R	
18-510315	19.50	14	36.3	166	146	28	8.0	4.5	23	1390	R	
18-510316	21.50	8	26.3	112	93	20	4.5	4.5	18	670	R	
18-510317	21.50	10	30.3	134	114	22	4.5	4.5	20	890	R	
18-510318	21.50	12	36.3	136	115	25	4.5	4.5	23	1200	R	
18-510319	21.50	14	36.3	166	145	28	8.0	4.5	23	1390	R	
18-510320	21.50	16	42.3	192	170	31	8.0	4.5	26	1840	R	
18-510321	23.50	8	26.3	114	94	20	4.5	4.5	18	680	R	
18-510322	23.50	10	30.3	134	113	22	4.5	4.5	20	890	R	
18-510323	23.50	12	36.3	138	116	25	4.5	4.5	23	1220	R	
18-510324	25.00	10	30.3	134	112	22	4.5	4.5	20	890	R	
18-510325	25.00	12	36.3	140	117	25	4.5	4.5	23	1240	R	
18-510326	25.00	14	36.3	166	143	25	4.5	4.5	23	1400	R	
18-510327	25.00	16	42.3	192	169	31	8.0	4.5	26	1850	R	
18-510328	25.00	18	48.3	211	187	34	8.0	4.5	29	2560	R	
18-510329	26.50	10	30.3	134	112	22	4.5	4.5	20	900	R	
18-510330	26.50	12	36.3	141	118	25	4.5	4.5	23	1250	R	
18-510331	26.50	14	36.3	166	143	25	4.5	4.5	23	1400	R	
18-510332	30.25	8	36.3	124	99	25	4.5	4.5	23	1120	R	
18-510333	30.25	10	36.3	138	113	25	4.5	4.5	23	1210	R	
18-510334	30.25	12	36.3	145	120	25	4.5	4.5	23	1280	R	
18-510335	30.25	14	36.3	168	143	25	4.5	4.5	23	1420	R	
18-510336	30.25	16	42.3	192	166	28	4.5	4.5	26	1860	R	
18-510337	33.50	8	36.3	127	100	25	4.5	4.5	23	1140	R	
18-510338	33.50	10	36.3	141	114	25	4.5	4.5	23	1230	R	
18-510339	33.50	12	36.3	148	121	25	4.5	4.5	23	1300	R	
18-510340	33.50	14	36.3	171	144	25	4.5	4.5	23	1440	R	
18-510341	33.50	16	42.3	192	164	28	4.5	4.5	26	1870	R	
18-510342	33.50	18	48.3	211	182	31	4.5	4.5	29	2590	R	

NOTES:

1. MATERIAL: CARBON STEEL
2. FINISH: HIGH HEAT ALUMINUM PAINT
3. FLANGED CONNECTION PER ANSI B16.5 SPECIFICATION
4. INLET AND OUTLET HAVE (2) 3/4 INCH NPT HALF COUPLING AND (1) M18 X 1.5 HALF COUPLING